



REVISIONS					
LTR	DESCRIPTION	DATE	REV.	CHKD.	APVD.

PCB LAYOUT(TOP VIEW) t=1.6mm  
NOTE:GENERAL TOLERANCE:±0.1mm

- SPECIFICATIONS:
- ELECTRICAL CHARACTERISTICS:
    - RATING: 50V, 0.2A Min.
    - CONTACT RESISTANCE: 20 mΩMax.
    - INSULATION RESISTANCE: 1000 MΩ Min.
    - DIELECTRIC WITHSTANDING VOLTAGE: 500V RMS AFTER 1 MINUTE.
  - MECHANICAL CHARACTERISTICS:
    - INSERTION FORCE : 35N Max.
    - WITHDRAWAL FORCE : 10N Min.
  - LIFE TEST: 1,500 CYCLES MIN.
  - PART MUST COMPLY ROHS SPECIFICATION.

3	SHELL	1	BRASS t=0.3	Ni PLATED	
2	TERMINAL	4	BRASS t=0.25	Au/Sn PLATED	
1	HOUSING	1	PBT	Black	
LTR	PART NAME	Q'TY	MATERIAL	REMARK	
120~315	±0.50	DWN	王安盛	DATE 2017.10.21	SCALE 4/1 PROJECTION CAT. NO. KMUSBA003AF04S1BY DWN.NO. A-USBA003AF04S1BY
30~120	±0.35	DSND	王安盛	DATE 2017.10.21	
6~30	±0.22	CHKD	李阮龍	DATE 2017.10.21	
BELOW 6	±0.16	APVD	郭遠峰	DATE 2017.10.21	
DIMENSION	TOLERANCE	KUNMING ELECTRONICS CO.,LTD.			1/1 001

The raw material specified by Sony should meet SS-00259 requirement of the latest version. When such material is used, it should be supplied by Sony designated suppliers.