



REVISIONS					
LTR	DESCRIPTION	DATE	REV.	CHKD.	APVD.

PCB LAYOUT(TOP VIEW) t=1.6mm
NOTE:GENERAL TOLERANCE:±0.1mm

- SPECIFICATIONS:
- ELECTRICAL CHARACTERISTICS:
 - RATING: 50V, 0.2A Min.
 - CONTACT RESISTANCE: 20 mΩMax.
 - INSULATION RESISTANCE: 1000 MΩ Min.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V RMS AFTER 1 MINUTE.
 - MECHANICAL CHARACTERISTICS:
 - INSERTION FORCE : 35N Max.
 - WITHDRAWAL FORCE : 10N Min.
 - LIFE TEST: 1,500 CYCLES MIN.
 - PART MUST COMPLY ROHS SPECIFICATION.

3	SHELL	1	FERRO ALLOY t=0.3	Ni PLATED
2	TERMINAL	4	BRASS t=0.25	Au/Sn PLATED
1	HOUSING	1	PBT	Black
LTR	PART NAME	Q'TY	MATERIAL	REMARK
120~315	±0.50	DWN	王安盛	DATE 2017.10.21
30~120	±0.35	DSND	王安盛	DATE 2017.10.21
6~30	±0.22	CHKD	李阮龍	DATE 2017.10.21
BELOW 6	±0.16	APVD	郭遠峰	DATE 2017.10.21
DIMENSION	TOLERANCE	KUNMING ELECTRONICS CO.,LTD.		SCALE 4/1
				PROJECTION
				CAT. NO.
				KMUSBA003AF04S1BYF
				DWN.NO.
				A-USBA003AF04S1BYF
				1/1
				001

The raw material specified by Sony should meet SS-00259 requirement of the latest version. When such material is used, it should be supplied by Sony designated suppliers.